

www.mellios.com.gr

TECHNICAL FILE

Skylux® EP10 PC

Polycarbonate skylight


SKYLUX
Hello daylight!



General product description

The Skylux® EP10 skylight consists standard of three plastic shells. A clear solid polycarbonate outer shell, a clear 10 mm structured polycarbonate middle sheet, an opal solid acrylic middle shell.

Due to its unique combination of solid and structured sheets an exceptional U value is obtained. The Skylux® EP10 polycarbonate skylight is finished and must be installed as any other standard Skylux® skylight and fits any Skylux® curb. The Skylux® EP10 polycarbonate is burglar proof.

The Skylux® EP10 polycarbonate skylight has the CE label according to EN 1873:2014+A1:2016.

Specific characteristics

Mechanical characteristics Polycarbonate (SPC10)	Impact resistance: 250 times stronger than glass of equal thickness. No damage on shocks similar to an impact of a steel ball of 250 gr falling from a height of 1 m. (hard body impact test according to EN 1873:2014+A1:2016) SB 1200 (soft body impact test according to EN 1873:2014+A1:2016)
---	---

U value (W/m²K), sound insulation (dB), light transmission (LT %) and solar heat gain factor (g %) in function of the type of skylight.

EP10 PC	
Type	AEO
U _t value* according to EN 673	1.30 W/m ² K
Sound insulation R _w according to EN ISO 140-3	21 dB
Light transmission LT according to EN 410	50%
Solar factor g (ZTA) according to EN 410	0.41 (41%)

*A Clear shell polycarbonate
E polycarbonate sheet 10 mm (4-walled)
O Opal shell acrylic*

*The reflection of the visible light can be calculated as 100 -LT (%)
The reflection of the total solar energy can be calculated as 100 -g (%)*

* U_t: U (transparent) value or insulation value of the Skylux skylight according to EN 1873:2014+A1:2016 determined according to EN 673

Attestations and certificates

- CE according to EN 1873:2014+A1:2016
- Declaration of Performance DoP n° 002DoP2013-05
- Sound insulation values R_w according to EN ISO 140-3 (report P902622-B)
- 1200 Joule certificate Cebtp D313.9.823.1/2 and SB 1200 (EN 1873:2014+A1:2016)

Fire reports

- Acrylic shell E (EN 13501-1)
- Polycarbonate shell M2 (NF P.92.507)
- Polycarbonate shell Class 1Y (BS 476)
- Polycarbonate shell B, S1-d0

www.mellios.com.gr

www.mellios.com.gr

Αποκλειστική διάθεση για την Ελλάδα



ΦΡΑΓΚΩΝ 14 - 546 26 ΘΕΣΣΑΛΟΝΙΚΗ
ΤΗΛ.: 2310 512 315, 512 818, FAX: 2310 532 372
www.mellios.com.gr • e-mail: info@mellios.com.gr

SKYLUX IS A REGISTERED BRAND OF AG.PLASTICS
SPINNERIJSTRAAT 100 - B-8530 STASEGEM
T +32 (0)56 20 00 00 - F +32 (0)56 21 95 99
INFO@SKYLUX.BE
WWW.SKYLUX.BE

